

NITRILE	BLUE	REF: NB15	S-XXL	FLOCKLINED
----------------	-------------	------------------	--------------	-------------------

Premium grade acrylonitrile butadiene rubber. Excellent resistance against aromatic and petroleum solvents and animal fats. It offers protection against to high variety of chemicals and against solvents in contact. Embossed pattern for sustained grip in wet and oily environment. Food handling or processing application.

Characteristics:

It doesn't contain latex protein. Suitable for latex allergic people.	Raised diamond pattern for better sustained grip.
Blue. Available in green	Flocklined
Resistance to oils and petroleum	Microbiological risks (bacteria, fungi and virus)
Silicone Free	Abrasion and resistance against certain chemicals

Presentation:

- Carton 144 pairs.
- Individual bag
- 12 packs x 12 pairs: total 144 pairs
- Dimension bag: 390 x 150 x 10 mm



Labelling: Manufacturing date, expiration date, batch number, reference, and EAN code. Product name in several languages: Spanish, English, French, German, Italian, Portuguese etc..

Ce marking, Protection Pictograms, Safety Standars and legislation. Size and units, size guide.

Gloves Dimensions	S	M	L	XL	XXL
Lenght	Min 330 mm	Min 330 mm	Min 330 mm	Min 330 mm	Min 330 mm
Thickness palm mm (± 0.02)	0.40	0.40	0.40	0.40	0.40



RUBBEREX SPAIN S.L

Regulations:

Regulation (EU) 2016/425. Personal protective equipment repealing Council Directive 89/686/EEC.

EN ISO 21420:2020

EN 388:2016+A1:2018. Protection against mechanical hazards.

A: Abrasion resistance (performance level 0 to 4).

B: Resistance to cutting by blade (performance level 0 to 5).

C: Resistance to tearing (performance level 0 to 4).

D: Puncture resistance (performance level 0 to 4)

E: Resistance to sharp cut (level A to F) X means not tested.

Chemical resistance:

PERMEATION EN 16523-1:2015. CHEMICAL HAZARDS EN ISO 374-1:2016+A1:2018

Gloves are classified in terms of breakthrough time, according to each individual chemical for which the glove resists permeation.

The gloves are tested against the following chemicals:

CHEMICALS	LETTER	LEVEL
METHANOL	A	2
N-HEPTANE	J	6
40% SODIUM HIDROXIDE	K	6
96% SULPHURIC ACID	L	3
AMMONIA 25%	O	3
37% FORMALDEHYDE	T	6
30% HYDROGEN PEROXIDE	P	6

Performance

Level:

time (min)	> 10	> 30	> 60	> 120	> 240	> 480
Level	1	2	3	4	5	6

DEGRADATION

Degradation % (DR) is determined for each chemical made in the permeation.

(DR) A: Methanol= 76.67%

(DR) J: n-Heptane= 38.81%

(DR) K: Sodium Hidroxide 40% = -25.55%

(DR) L: Sulphuric Acid 96% = 96.68%

RUBBEREX SPAIN S.L

(DR) O: Ammonia 25% = 13.43%

(DR) P: Hydrogen Peroxide 30% = 19.64%

(DR) T: Formaldehyde 37% = 10.58 %


The PPE NB15 should be used to protect the user's hand against chemical risks (products mentioned above) and against microbiological risks bacteria, fungi and virus.

The present PPE should be used against other risks than those described above. The use of this PPE should be evaluated correctly depending on the place of work.

EN 388: 2016+A1:2018

EN ISO 374-1:2016 / Tipo A

EN ISO 374-5:2016



2001X



A J K L O T



REF	Colour	Size	Size number	EAN
0723	BLUE	S	7	9556073307238
0724	BLUE	M	8	9556073307245
0725	BLUE	L	9	9556073307252
0726	BLUE	XL	10	9556073307269
0727	BLUE	XXL	11	9556073307276

packing



Logistic:

BOX: 144 guantes

PACK: 12 pares

Pallet: 40 cajas

Rev 007 MAYO 2023

RUBBEREX SPAIN S.L

+34 96 166 7124

info@rubberex.es

www.rubberex.es

Polígono Industrial Masía del Baló. C/Mas Vallesa de Mandor N8 Nave12. CP. 46190. Ribarroja del Turia. Valencia. España