

NEOPRENE/LATEX	BLACK	REF: HD27	S-XXL	FLOCKLINED
----------------	-------	-----------	-------	------------

Latex neoprene, heavy weight industrial rubber glove. Specially blended rubber compound. Excellent grip in wet and oily environment. Available in orange.

### Characteristics:

Contain latex protein. Not suitable for latex allergic people.	Raised diamond pattern for better sustained grip.
Resistance of neoprene and comfort of latex	Resistance oil and facts
Flock line. Interior for comfort.	Excellent grip
Chloroprene coated over natural rubber	Abrasion and resistance against certain chemicals

### Presentación:

- Carton 100 pairs.
- Individual bag
- 10 packs x 10 pairs: total 100 pairs
- Dimension bag: 390 x 140 x 20 mm



**Labelling:** Manufacturing date, expiration date, batch number, reference, and EAN code. Product name in several languages: Spanish, English, French, German, Italian, Portuguese etc.

Ce marking, Protection Pictograms, Safety Standars and legislation. Size and units, size guide.

Gloves Dimensions	S	M	L	XL	XXL
<b>Lenght</b>	Min 320 mm	Min 320 mm	Min 320 mm	Min 320 mm	Min 320 mm
<b>Thickness palm mm (± 0.02)</b>	0.68	0.68	0.68	0.68	0.68



RUBBEREX SPAIN S.L

+34 96 166 7124

✉ [info@rubberex.es](mailto:info@rubberex.es)

[www.rubberex.es](http://www.rubberex.es)

📍 Polígono Industrial Masía del Baló. C/Mas Vallesa de Mandor N8 Nave12. CP. 46190. Ribarroja del Turia. Valencia. España



## NORMATIVE

This glove is in conformity according Regulation (EU) 2016/425 on personal protective equipment.

The protective glove complies with the following European standards:

EN ISO 21420:2020

EN ISO 374-1:2016+A1:2018

EN 388:2016 + A1:2018 Mechanical hazards

EN ISO 374-5:2016

## CHEMICAL RESISTANCE.

PERMEATION. ISO 374-1:2016+A1:2018 – EN 16523-1:2015

Gloves are classified in terms of time of passage, according to each individual chemical for which the glove resists permeation.

The gloves are tested against the following chemicals:

CHEMICALS	LETTER	LEVEL
METHANOL	A	3
N-HEPTANE	J	2
SODIUM HIDROXIDE 40%	K	6
SULPHURIC ACID 96%	L	4
ACETIC ACID 99%	N	3
HYDROGEN PEROXIDE 30%	P	6
FORMALDEHYDE 37%	T	6

Performance

Level:

time (min)	> 10	> 30	> 60	> 120	> 240	> 480
Level	1	2	3	4	5	6

## **DEGRADATION**

Degradation % (DR) is determined for each chemical made in the permeation.

(DR) A: Methanol = 25.5%

(DR) J: n-Heptane = 78.5%

(DR) K: Sodium Hidroxide 40% = - 4,3%

(DR) L: Sulphuric Acid 96% = 34.9%

(DR) N: Acetic Acid 99% = 34.9

(DR) P: Hydrogen Peroxide 30%: 0.3%

(DR) T: Formaldehyde 37% = -1.0 %

The HD27 PPE should be used to protect the user's hand against chemical risks (products mentioned above) and against microbiological risks bacteria and fungi

RUBBEREX SPAIN S.L



The present PPE should be used against other risks than those described above. The use of this PPE should be evaluated correctly depending on the place of work

EN 388: 2016+A1:2018



2121X

EN ISO 374-1:2016+A1:2018 / Type A



A J K L N P T

EN ISO 374-5:2016



VIRUS



CAT III



2777

REF	Colour	Size	Size number	EAN
0228	BLACK	S	7	9556073213218
0229	BLACK	M	8	8435234001530
0230	BLACK	L	9	8435234001547
0231	BLACK	XL	10	9556073213249
0232	BLACK	XXL	11	9556073213256

## packing



## Logistic:

Carton: 100 pairs

Pack: 10 pairs

Pallet: 40 cartons